



US008896580B2

(12) **United States Patent**
Doczy et al.

(10) **Patent No.:** **US 8,896,580 B2**
(45) **Date of Patent:** **Nov. 25, 2014**

(54) **INSTRUMENT-ACTIVATED SUB-SURFACE
COMPUTER BUTTONS AND SYSTEM AND
METHOD INCORPORATING SAME**

(2013.01); *G06F 1/169* (2013.01); *G06F*

1/1669 (2013.01); *G06F 3/041* (2013.01);

G06F 1/166 (2013.01); *G06F 1/1656* (2013.01)

USPC 345/179; 345/156; 345/183

(71) Applicant: **Hewlett-Packard Development
Company, L.P.**, Fort Collins, CO (US)

(58) **Field of Classification Search**

USPC 345/173, 156; 178/18.01

See application file for complete search history.

(72) Inventors: **Paul J Doczy**, Cypress, TX (US); **Stacy
Wolff**, Cypress, TX (US); **Steven S
Homer**, Cypress, TX (US); **Mark C
Solomon**, Cypress, TX (US)

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,672,154	A	6/1987	Rodgers et al.	
4,686,332	A *	8/1987	Greanias et al.	345/173
4,730,186	A	3/1988	Koga et al.	
5,049,862	A	9/1991	Dao et al.	
5,067,573	A	11/1991	Uchida	
5,177,328	A	1/1993	Ito et al.	
5,180,891	A	1/1993	Trumbo	
5,231,381	A *	7/1993	Duwaer	345/174
5,369,227	A	11/1994	Stone	
5,389,745	A	2/1995	Sakamoto	

(Continued)

Primary Examiner — M Good Johnson

(73) Assignee: **Hewlett-Packard Development
Company, L.P.**, Houston, TX (US)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 0 days.

(21) Appl. No.: **13/860,430**

(22) Filed: **Apr. 10, 2013**

(65) **Prior Publication Data**

US 2013/0229393 A1 Sep. 5, 2013

Related U.S. Application Data

(62) Division of application No. 10/160,201, filed on May
31, 2002, now Pat. No. 8,446,359.

(51) **Int. Cl.**
G06F 3/033 (2013.01)
G09G 5/00 (2006.01)
G09G 3/22 (2006.01)
G06F 1/16 (2006.01)
G06F 3/0354 (2013.01)
G06F 3/0488 (2013.01)
G06F 3/041 (2006.01)

(52) **U.S. Cl.**
CPC *G06F 3/03545* (2013.01); *G06F 2200/1634*
(2013.01); *G06F 2200/1614* (2013.01); *G06F*
1/1671 (2013.01); *G06F 1/1626* (2013.01);
G06F 1/1632 (2013.01); *G06F 3/04886*

(57) **ABSTRACT**

The present technique provides a system and method for providing instrument-activated buttons having a sub-surface mechanism for triggering a desired function upon interaction with an above-surface electronic/digital user device, such as a digitizing pointing device. The instrument-activated buttons may be disposed in a display device, a tablet computing device, or any other suitable electronic device. A user navigates a housing surface of the electronic device until a signal identifies the sub-surface button, which may then be activated by performing an instrument-based activation event. The activation event may be a button click, a tip movement, or any other suitable trigger on the electronic/digital user device. A wireless communication is then transmitted between the sub-surface mechanism and the electronic/digital user device to initiate the function associated with the instrument-activated button.

17 Claims, 24 Drawing Sheets

